

5

APPLICATION FOR UNITED STATES LETTERS PATENT

10

for

**IMPROVED CHEMICAL MECHANICAL POLISHING COMPOSITIONS FOR METAL
AND ASSOCIATED MATERIALS AND METHOD OF USING SAME**

15

by

20

Ying Ma

William Wojtczak

Cary Regulski

25

Thomas H. Baum

David D. Bernhard

and

Deepak Verma

Technical Field of the Invention

The present invention relates generally to the chemical mechanical polishing of semiconductor devices systems and methods, and more particularly, to a formulation and method for use in polishing metal
5 films in semiconductor interconnection processes.

Background of the Invention

The present invention relates to a chemical mechanical polishing composition for surfaces of a
10 semiconductor wafer, and more particularly, to a chemical mechanical polishing slurry and a method for using the slurry to remove and polish copper containing materials, barrier materials and dielectric materials layered on semiconductor wafer surfaces.

Semiconductor wafers are used to form integrated circuits. The semiconductor wafer typically
15 includes a substrate, such as silicon, upon which dielectric materials, barrier materials, and metal conductors and interconnects are layered. These different materials have insulating, conductive or semi-conductive properties. Integrated circuits are formed by patterning regions into the substrate and depositing thereon multiple layers of dielectric material, barrier material, and metals.

In order to meet the higher speeds required in LSI, semiconductor manufacturers are looking to copper
20 and its alloys as interconnect materials due to its decreased resistivity. Copper is also less vulnerable to electromigration than other metals such as aluminum and less likely to fracture under stress.

In conventional deposition, a layer of metal and a layer of a masking material called photoresist are
25 deposited on a silicon wafer. Unwanted metal is then etched away with an appropriate chemical, leaving the desired pattern of wires or vias. Next, the spaces between the wires or vias are filled with silicon dioxide (an insulator), and finally the entire wafer surface is polished to remove excess insulator. In copper deposition the damascene method is used wherein an oxide layer is first deposited and the pattern of wires or vias is formed by etching the oxide. The metal is then deposited second.

As successive layers are deposited across previously patterned layers of an integrated circuit,
30 elevational disparity or topography develops across the surface of each layer. If left unattended, the elevational disparities in each level of an integrated circuit can lead to various problems. For example, when

dielectric, conductive, or semiconductive material is deposited over a topological surface having elevationally raised and recessed regions, step coverage problems may arise. Step coverage is defined as a measure of how well a film conforms over an underlying step and is expressed by the ratio of the minimum thickness of a film as it crosses a step to the nominal thickness of the film over horizontal regions.

Typically for copper technology, the layers that are removed and polished consist of a copper layer (about 1-1.5 μm thick) on top of a thin copper seed layer (about 0.05-0.15 μm thick). These copper layers are separated from the dielectric material surface by a layer of barrier material (about 50-300 \AA thick).

In order to obtain the correct patterning, excess material used to form the layers on the substrate must be removed and or planarized. Further, to obtain efficient circuits, it is important to have a flat or planar semiconductor wafer surface. Thus, it is necessary to polish certain surfaces of a semiconductor wafer.

Chemical Mechanical Polishing or Planarization ("CMP") is a process in which material is removed from a surface of a semiconductor wafer, and the surface is polished (planarized) by coupling a physical process such as abrasion with a chemical process such as oxidation or chelation. In its most rudimentary form, CMP involves applying slurry, a solution of an abrasive and an active chemistry, to a silicon wafer or polishing pad that buffs the surface of a semiconductor wafer to achieve the removal, planarization, and polishing process.

One key to obtaining good uniformity across the wafer surface is by a polishing formulation that has the appropriate selectivity for the material(s) to be removed. Good slurry distribution and uniform distribution of mechanical force are also key to obtaining good planarity. If appropriate film removal selectivity is not maintained dishing of copper and/or erosion of the dielectric may occur. Dishing may occur when the copper and barrier removal rates are disparate or when the chemistry is too active for the metal interconnect layer. Erosion occurs when the local dielectric removal rate is much higher than the metal rate (see Figures 1-5).

Typical commercial CMP slurries used to remove overfill material and polish semiconductor wafer surfaces have a barrier material removal rate below 500 $\text{\AA}/\text{min}$. Further, these slurries have a copper to barrier material removal rate selectivity of greater than 4:1. This disparity in removal rates during

the removal and polishing of the barrier material results in significant dishing of copper on the surface of the semiconductor wafer and/or poor removal of the barrier material.

As a potential solution, copper CMP often employs a two-step slurry approach. The slurry used in the first step is typically used to remove and planarize bulk copper and as such has a high copper removal rate, (e.g. 4000 Å/min) and a comparatively low barrier material removal rate (e.g. 500 Å/min). The slurry used in the second step is used for the barrier breakthrough step and finishing and as such has a relatively high barrier material removal rate (e.g. 1000 Å/min), comparable or lower removal rate for copper and low removal rate on the dielectric material, (e.g. the rates for copper and dielectric (thermal oxide) should be lower than 500 Å/min).

Currently, commercially available copper slurries use particles such as fumed or precipitated silica or alumina as abrasives. These abrasives typically have large particle size distributions when suspended in the slurries. Particles of fumed alumina and silica have diameters around 700 nm and particle size distributions of $> 1 \mu\text{m}$. Wide particle size distribution may significantly impact the planarization efficiency.

Fumed or precipitated silica or alumina may also agglomerate to form larger, dense, hard particles or agglomerated precipitates over time. (See U.S. 5,527,423 to Neville, et al.). This produces defects in the form of scratches, voids, defects or pits on the polished wafer surface.

Further, the abrasives are inorganic oxide particles that have high hardness. As a result, defects in the form of micro-scratches are produced on copper surfaces during and after polishing. The scratches occur due to the solid abrasive, in particular alumina, which is the main material used as a metal polishing abrasive. Slurry remains behind in the micro-scratches causing the semiconductor device to fail. Micro scratches and poor planarization efficiency result in integrated circuits with increased defects and a lower yield.

Current second step slurries suffer from a low selectivity of barrier to metal, the best selectivity being about 6 to 1, while the selectivity of barrier to dielectric is in the range of from about 2 to 27. (See U.S. 6,063,306 to Kaufman, et al.; 5,676,587 to Landers, et al.; 6,001,730 to Farkas, et al.; and 6,242,351 to Li, et al.).

Therefore, it is one object of the present invention to provide an improved slurry composition using an abrasive having a moderate hardness to remove a softer metal oxide layer while keeping the harder barrier layer and thermal oxide layer relatively intact.

5 It is a further object of this invention to provide an improved two step slurry approach using a first polishing slurry having a high removal rate on metal and a high selectivity of metal to barrier and a second slurry also called a barrier break-through step having a high removal rate on barrier and a low to moderate removal rate on copper and dielectric.

10 It is a further object of the present invention to provide a stable first-step polishing slurry comprising an abrasive that does not agglomerate over time to form hard, dense sediment.

A still further object of the present invention is to provide a stable first-step polishing slurry comprising a moderately hard abrasive having a minimal particle size distribution.

15 These and other objects and advantages of the invention will be apparent to those skilled in the art upon reading the following detailed description and upon reference to the drawings.

Summary of the Invention

20 The present invention is directed to a chemical mechanical polishing slurry comprising a first slurry, which has a high removal rate on copper and a low removal rate on barrier material and a second slurry, which has a high removal rate on barrier material and a low to moderate removal rate on copper and the associated dielectric material. The first slurry composition comprises at least a moderately
 25 hard organic polymeric abrasive, an oxidizing agent and an activating agent and the second slurry comprises at least a silica abrasive, an oxidizing agent and an activating agent. Also disclosed as the present invention, is a method for chemical mechanical polishing of copper, barrier material and dielectric material with the polishing slurry of the present invention. As will become apparent from the discussion that follows, the stable slurry and method of using the slurry provide for removal of
 30 material and polishing of semiconductor wafer surfaces with significantly no dishing, or oxide erosion, with significantly no surface defects and good planarization efficiency.

Brief Description of the Drawings

FIG. 1 is a cross-sectional view of a semiconductor wafer prior to chemical mechanical polishing.

FIG. 2 is a cross sectional view of the semiconductor wafer of FIG. 1 following chemical mechanical polishing with the first slurry, according to one embodiment of the present invention.

5

FIG. 3 is a cross sectional view of the semiconductor of Fig. 1 following chemical mechanical polishing with the first slurry, according to another embodiment of the present invention.

FIG. 4 is a cross sectional view of the semiconductor wafer of FIG. 2 following chemical mechanical polishing with the second slurry, according to the present invention.

10

FIG. 5 is a cross sectional view of a semiconductor wafer illustrating copper dishing.

FIG. 6 is a cross sectional view of a semiconductor wafer illustrating oxide erosion.

15

Detailed Description of the Invention and Preferred Embodiments Thereof

The disclosure of the following United States patent application, which is commonly owned by the assignee of the present application is hereby incorporated herein by reference in its entirety:

20 U.S. Patent Application No. 09/562,298 filed on May 1, 2000 in the names of Thomas H. Baum, et al.

The present invention presents a novel, stable chemical-mechanical polishing (CMP) slurry that overcomes the deficiencies in the prior art while providing a manufacturable process that may be implemented in the semiconductor-manufacturing arena with little or no alterations to the current CMP systems and footprints. As will become apparent from the examples that follow, the stable CMP slurry and method of using such slurry provide for removal of material and polishing of semiconductor wafer surfaces with significantly improved defectivity including reduced dishing or oxide erosion, with significantly no surface defects and good planarization efficiency.

25

30 The present invention provides a chemical mechanical polishing slurry composition and method of using such slurry for removing and polishing the bulk copper layer of a damascene processing step in the manufacturing of an integrated circuit. Further, the following invention provides a two step CMP slurry comprising a first slurry formulation, which has a high removal rate on copper and a low

removal rate on barrier material and a second slurry formulation that has a high removal rate on barrier material and a low to moderate removal rate on copper and the associated dielectric material.

FIG. 1 illustrates a semiconductor wafer **10** prior to CMP. As shown, substrate **11** may be made of any conventional semiconductor materials, including silicon, germanium or silicon-germanium. Layered on top of the substrate **11** is dielectric material **12**, which is preferentially silicon oxide, low k dielectrics comprised substantially of silicon oxide, a carbon containing silicon oxide or a fluoride doped silicon glass (FSG). Layered on the dielectric material **12**, is barrier material **13**. The barrier material layer **13** is typically about 50 to 300 Å thick. The barrier material **13** may be any material conventionally used, but is typically chosen from the group of tungsten nitride, tantalum, tantalum nitride, titanium nitride, silicon doped tantalum nitride or silicon doped titanium nitride. Finally, a layer of copper **14** covers the barrier material layer **13**, and extends into trenches **14a**, **14b**, and **14c**. The copper layer **14** is usually about 1-to 1.5 μm thick and the copper layer **14** in **FIG. 1** may include a thin copper seed layer, which is usually about 0.05-0.15 μm thick.

The invention is a CMP slurry designed to polish copper **14** and associated barrier materials **13** such as tungsten nitride, tantalum, tantalum nitride, silicon doped tantalum nitride, titanium nitride and silicon doped titanium nitride. The chemical mechanical polishing slurry of the present invention is comprised of two parts. The first slurry is a copper selective slurry formulation used to remove the bulk copper down to the barrier layer (**FIG. 2**). The first slurry has a high removal rate of copper and a low removal rate of barrier material. The second slurry formulation is selective to the barrier layer and removes the barrier material down to the dielectric material. The second slurry has a high removal rate of barrier and a low to moderate removal rate of copper and dielectric. (**FIG. 3**). The various removal rates of the first and second slurries on various materials are shown in Table 1. In this way, two slurries together comprise a combined package to polish copper metallization schemes for integrated circuit manufacturing.

Table 1. Removal Rates of the First and Second Slurries on Different Materials*

Layer	First Slurry Removal Rates (Å/min)	Selectivity First Step Cu to Material	Second Slurry Removal Rates (Å/min)	Selectivity Second Step Ta to Material
Copper	4100	—	1	60:1
Tantalum	<8.2	>500	60	—
Tantalum Nitride	<8.2	>500	81	—

Thermal Oxide	<8.2	>500	31	2:1
---------------	------	------	----	-----

*(For the first step, Down Force = 4 psi, Flow Rate = 160 mL/min, Table Speed = 125 rpm, Quill Speed = 116 rpm, Pad Type = IC 1000 Subpad: Suba IV, For the second step, Down Force = 4 psi, Flow Rate = 160 mL/min, Table Speed = 45 rpm, Quill Speed = 42 rpm, Pad Type = IC 1000, Subpad: Suba IV)

5

Referring to **FIG. 1**, In one embodiment, the present invention includes a method for chemical mechanical polishing copper **14**, barrier material **13** and dielectric material **12**, comprising the following steps: (1) providing a first chemical mechanical polishing slurry comprising an organic polymeric abrasive, wherein said first slurry has a high removal rate on copper **14** and a low removal rate on barrier material **13**; (2) chemical mechanical polishing a semiconductor wafer surface **10** with the first slurry; (3) providing a second chemical mechanical polishing slurry that has a high removal rate on barrier material **13** a low to moderate removal rate on copper **14** and a low to moderate removal rate on the dielectric material **12**; and (4) chemical mechanical polishing the semiconductor wafer surface **10** with the second slurry.

10

15

Generally, the slurry is applied to a pad contained on a polishing instrument or directly dispensed onto the wafer to be processed. Polishing instrument parameters such as down force (DF), flow rate (FR), table speed (TS), quill speed (QS), and pad type can be adjusted to effect the results of the CMP slurry. Preferably the down force is in a range from about 3 to 10 psi, the flow rate is in a range of from about 120 to 200 mL/min, the table speed is in a range of from about 35 and 200 rpm, a quill speed in a range of from about 30 to 200 rpm, and an IC 1000 pad type.

20

The polishing pad serves as a means of applying mechanical friction and adhesion to the wafer surface. The optimum hardness of the pad is different depending on the object on which CMP is being performed. In the instant invention, a hard polishing pad is preferred, such as the type manufactured by Rodel, 3804 East Watkins Street, Phoenix, AZ 85034 and sold under the brand name IC 1000.

25

According to one embodiment of the present invention, **FIG. 2** illustrates the semiconductor wafer **10** of **FIG. 1**, after steps (1) and (2) of the present method for CMP have been carried out, and the semiconductor wafer surface has been polished with the first slurry. When **FIG. 2** is compared to **FIG. 1**, the top copper layer **14** in **FIG. 1** has been preferentially removed, and only the copper in the trenches (**FIG. 2**) **18a**, **18b**, and **18c** is left. As shown in **FIG. 2** the barrier material layer **17** is substantially in tact, and the dielectric material **16** based on substrate **15** is still unexposed.

30

35

According to a further embodiment of the present invention, **FIG. 3** illustrates the semiconductor wafer **10** of **FIG. 1**, after steps (1) and (2) of the present method for CMP have been carried out, and the semiconductor wafer surface has been over-polished with the first slurry in order to remove all the bulk copper on top of the barrier layer, while leaving the barrier layer relatively in tact. When **FIG. 3** is compared to **FIG. 1**, the top copper layer **14** in **FIG. 1** has been preferentially removed, and only the copper in the trenches (**FIG. 3**) **20a**, **20b**, and **20c** is left. As shown in **FIG. 3** the barrier material layer **21** is substantially in tact, and the dielectric material **22** based on substrate **23** is still unexposed.

Similarly, **FIG. 4** illustrates the semiconductor wafer **10** of **FIGS. 1** and **2** and **3**, after steps (3) and (4) of the present method for CMP have been carried out, and the semiconductor wafer surface has been polished with the second slurry. As shown in **FIG. 4**, the barrier material layer **24** has been removed down to the dielectric material **25**. The second slurry also removed just enough of the copper in trenches **26a**, **26b**, and **26c** so that the surface of the semiconductor wafer **10** is flat and planar. The second slurry also serves to polish the newly exposed surface, including the dielectric material **25**, the barrier material **24a**, **24b**, **24c**, and the copper **26a**, **26b**, **26c**. All of these materials are based on substrate **27**.

By using the first and second step slurry compositions of the claimed invention, with the selectivities described in Table 1, and following the described method, copper dishing (**FIG. 5**) and oxide erosion (**FIG. 6**) can be minimized. **FIG. 5** shows a semiconductor wafer to which a CMP slurry has been applied, which had a higher selectivity for copper **28a**, **28b**, **28c** than for the barrier material **29a**, **29b**, **29c** or dielectric material **30**. As a result, disparate amounts of copper are removed from the surface of the semiconductor wafer. This is known as copper dishing and is shown by the dish-like troughs **31a**, **31b**, and **31c** in the trenches of copper **28a**, **28b**, **28c**. The CMP slurry of the present invention and method of using this slurry greatly reduces copper dishing.

Similarly, **FIG. 6** shows a semiconductor wafer to which a CMP slurry has been applied, which has a higher selectivity for the dielectric material **32** than for the barrier material **33a**, **33b**, **33c**, or copper **34a**, **34b**, **34c**. As a result, disparate amounts of dielectric material are removed from the surface of the semiconductor wafer. This is known as oxide erosion and is shown by the indentions and/or reduction of the dielectric material **32a**, **32b**. The CMP slurry of the present invention and method of using this slurry greatly reduces oxide erosion.

The present invention provides a novel first-step slurry polishing composition comprising an organic polymeric abrasive having little or no agglomeration over time.

International patent PCT/US00/17046 teaches that agglomeration of abrasive particles occurs in two stages. Stage 1 agglomeration involves agglomerated particles held together primarily by van der Waals forces. Stage 2 agglomeration can occur after stage 1 agglomeration, wherein the particles then fuse together over time, causing the particles to be primarily held together not by van der Waals forces, but rather by covalent (or similar-type high energy) bonding between the particles. The present first step slurry formulation avoids stage 1 and stage 2 agglomeration.

In one embodiment, the present invention provides a CMP slurry comprising a first step slurry composition useful for removal, planarization and polishing of metal layers from a semiconductor substrate. The composition comprises a novel organic polymeric abrasive that is moderately hard and does not agglomerate in the formulation over time or during use. The moderately hard nature of the polymeric abrasive provides for the removal of the softer copper layer while keeping the harder barrier and thermal oxide layer relatively intact.

The abrasive component of the first step slurry may comprise any polymeric material that is sufficiently hard to abrade copper oxide, in any shape or form that sufficiently abrades the metal and/or metal oxide layer from the substrate surface. Specific examples of polymeric materials useful as abrasive components include but are not limited to poly (styrenes), poly (ethers), poly (siloxanes), poly (vinyl acetates), poly (vinyl alcohols), poly (vinylbenzenes), and substituted versions and mixtures thereof. Colloidal solutions of these polymer solutions are available from Polysciences, Polymer Systems AS, and Microparticles GmbH. Raw materials to manufacture these particles are widely commercially available in the paper industry as paper surface sizing agents.

In a preferred embodiment, the CMP slurry comprises a first slurry polishing formulation useful for removal and polishing of copper containing materials from a semiconductor substrate, wherein the formulation comprises poly (methyl methacrylate) as the abrasive. Preferably, the poly (methyl methacrylate) particles have a particle size distribution in the range of from about 3 to 100 nm, more preferably from about 15 to 80 nm and most preferably from about 30 to 60 nm. Preferably the mean particle size distribution of the poly (methyl methacrylate) particles is in a range of from about 20 to 80 nm, more preferably from about 30 to 60 nm and most preferably the mean particles size is

between about 40 and 45 nm. Preferably the specific gravity of the particles is between 1 and 1.5 g/mL.

The poly (methyl methacrylate) or other polymeric abrasive particles of the present invention have an aggregate size distribution of less than 1.0 micron and an average or mean aggregate diameter of less than about 45 nm. These abrasive particles have a much milder hardness compared to alumina and silica abrasives.

The first step slurry, thus, can employ polymeric constituents as the abrasive particles in the size range of 3 to 100 nm. These particles coupled with the step 1 formulation chemistry described below, allow the first-step slurry to achieve a high copper removal rate but a minimal barrier material removal rate. Poly (methyl methacrylate), with a narrow size distribution, minimizes micro scratch defects and provides superior removal rates on copper materials, greater than about 1000 Å/min, more preferably greater than about 2000 Å/min and most preferably greater than about 4000 Å/min and low removal rates for barrier and dielectric. Further, such abrasives with a mean size of less than about 45 nm provide very good planarization efficiency without increased defectivity.

In a further embodiment the CMP slurry comprises a first step slurry polishing formulation for removing a copper containing layer from a substrate, said formulation comprising a polymeric abrasive, oxidizing agent and activating agent. Preferably the formulation has a pH in a range of from about 0.1 to 6.9, more preferably in the range from about 1 to 5 and most preferably, the pH of the polishing formulation is in the range of from about 2 to 4.8. The pH of the solution is critical to achieving acceptable removal rates.

As used herein, the term oxidizing agent is defined as any substance which removes metal electrons and raises the atomic valence and includes but is not limited to hydrogen peroxide (H_2O_2), ferric nitrate ($\text{Fe}(\text{NO}_3)_3$), potassium iodate (KIO_3), potassium permanganate (KMnO_4), nitric acid (HNO_3), ammonium chlorite (NH_4ClO_2), ammonium chlorate (NH_4ClO_3), ammonium iodate (NH_4IO_3), ammonium perborate (NH_4BO_3), ammonium perchlorate (NH_4ClO_4), ammonium periodate (NH_4IO_4), ammonium persulfate ($(\text{NH}_4)_2\text{S}_2\text{O}_8$), tetramethylammonium chlorite ($(\text{N}(\text{CH}_3)_4\text{ClO}_2$), tetramethylammonium chlorate ($(\text{N}(\text{CH}_3)_4\text{ClO}_3$), tetramethylammonium iodate ($(\text{N}(\text{CH}_3)_4\text{IO}_3$), tetramethylammonium perborate ($(\text{N}(\text{CH}_3)_4\text{BO}_3$), tetramethylammonium perchlorate ($(\text{N}(\text{CH}_3)_4\text{ClO}_4$), tetramethylammonium periodate ($(\text{N}(\text{CH}_3)_4\text{IO}_4$), tetramethylammonium persulfate

$((\text{N}(\text{CH}_3)_4)_2\text{S}_2\text{O}_8)$, urea hydrogen peroxide $((\text{CO}(\text{NH}_2)_2)_2\text{H}_2\text{O}_2)$. The preferred oxidizing agents for the first-step slurry composition of the instant invention are hydrogen peroxide and iodate salts.

Alternatively, the oxidizing agent may comprise an amine-N-oxide having the formula $(\text{R}_1\text{R}_2\text{R}_3\text{N}\rightarrow\text{O})$, wherein $\text{R}_1\text{R}_2\text{R}_3$ are independently selected from the group consisting of: H and $\text{C}_1\text{-C}_8$ alkyl. Specific examples of amine-N-oxides include but are not limited to 4-methylmorpholine N-oxide ($\text{C}_5\text{H}_{11}\text{NO}_2$) and pyridine-N-oxide ($\text{C}_5\text{H}_5\text{NO}$).

Further, as used herein, the term activating agent is defined as any substance that in the presence of a water containing solution solubilizes or etches the oxidized copper material. Copper activating agents useful in the present invention include but are not limited to mineral acids (*i.e.* hydrochloric acid, nitric acid), inorganic acids (*i.e.* phosphoric acid) and organic acids (*i.e.* citric acid, acetic acid and maleic acid). Preferably the activating agent of the present first step slurry is citric acid.

In a further embodiment, the first step slurry composition of the present invention, may comprise, a polymeic abrasive, an oxidizing agent, an activating agent, a corrosion inhibitor and optionally a cleaning agent. Preferably the first-step slurry composition comprises from about 0.1 to 50 percent colloidal poly (methyl methacrylate), from about 0.1 to 25 percent oxidizing agent; from about 0 to 5 percent activating agent; from about 0 to 3 percent corrosion inhibitor and from about 0 to 3 percent cleaning agent. Preferably the pH of the first-step slurry composition is between about 0.1 to 6.9 and more preferably between about 1 to 5.

As used herein, a corrosion inhibitor is defined as a substance that reacts with the fresh copper surface and/or oxidized copper thin film to passivate the copper layer and prevent excessive etching of the copper surface during CMP. The first slurry of the present invention is sufficiently benign to the metal surface being polished to have a static metal etch rate of less than 500 Å, more preferably less than 200 Å, and most preferably less than 50 Å.

As used herein, a cleaning agent is defined as a substance that slowly etches, or chelates to the the copper, leading to soluble copper complexes that can be readily removed during polishing.

The corrosion inhibitor should be a carboxylic acid. More specifically, the carboxylic acid may be chosen from the group of glycine, oxalic acid, malonic acid, succinic acid and nitrilotriacetic acid. Alternatively, the carboxylic acid may be a dicarboxylic acid that preferentially has a nitrogen

containing functional group. In the most preferred form, the corrosion inhibitor is iminodiacetic acid or benzotriazole.

5 The first step slurry formulation may further comprise potassium or ammonium hydroxide or other buffering agents in such amounts as to adjust the pH to the desired level.

10 In a preferred embodiment, the first step slurry formulation is an aqueous mixture comprising (by weight percentage) 5 percent poly (methyl methacrylate) as the abrasive or 12.5 percent colloidal poly (methyl methacrylate) as abrasive; 0.1 percent of citric acid as activating agent; and 0.2 percent iminodiacetic acid as passivating agent. Ammonium hydroxide was used to adjust the pH to the desired level.

15 The abrasive used in the preferred first-step slurry formulation of the present invention may be stabilized with a surfactant. The surfactant may be cationic or anionic. Preferably the surfactant is anionic. The surface charges that the surfactant imparts to the particles cause steric repulsion among the abrasive particles in order to keep the particles suspended in a colloidal state within the slurry composition.

20 Anionic surfactants are ionic compounds, with the anion being the surface-active portion. In the present invention the surfactant is selected from the group consisting of alkyl sulfates, carboxylates and alkyl phosphates having carbon backbones in the range of from C10 to C14. Preferably the surfactant is a sulfate. More preferably the surfactant is sodium laurel sulfate.

25 By coating the abrasive particles with a surfactant or polyelectrolyte prior to incorporating the particles into a slurry system or after the particles are incorporated into a system, stage 2 agglomeration may be inhibited. The surfactant and/or polyelectrolyte will tend to remain in close proximity to the slurry particles, thereby sterically hindering the particles from coming sufficiently close to one another to enable stage 2 agglomeration.

30 During the damascene process, grooves are dry etched into an insulating thin film to form an interconnect pattern. Copper or copper alloy is deposited over the entire wafer surface, reflecting the groove which is the interconnect pattern. If left unattended, the elevational disparities in each level of an integrated circuit can lead to various problems. For example, when dielectric, conductive, or semiconductive material is deposited over a topological surface having elevationally raised and

recessed regions, step coverage problems may arise. Step coverage is defined as a measure of how well a film conforms over an underlying step and is expressed by the ratio of the minimum thickness of a film as it crosses a step to the nominal thickness of the film over horizontal regions.

5 Although the organic polymeric abrasive particles of the present invention have been directed to poly (methyl methacrylate), it is understood that the teachings herein have applicability to other organic polymeric materials such as poly (styrenes), poly (ethers), poly (siloxanes), poly (vinyl acetates), poly (vinyl alcohols), poly (ethylenes), poly (imides), poly (vinylbenzenes), and substituted versions thereof. Further, the organic polymeric abrasive particles may be utilized to polish other metal surfaces
 10 such as tungsten, aluminum and titanium as well as under layers such as titanium, titanium nitride and alloys of titanium/tungsten.

As described hereinabove the present invention provides a chemical mechanical polishing first-step slurry formulation for removing and polishing the bulk copper layer of a damascene processing step in
 15 the manufacturing of an integrated circuit.

At the end of the first step, the bulk copper material layer has been removed exposing the underlying barrier layer. A second-step slurry is useful to remove the barrier layer and to complete the planarization of the wafer surface.
 20

In the second step polishing which is also called a barrier break through step, a high removal rate for barrier (i.e. Ta or TaN) and a high selectivity of barrier to copper and to dielectric is desirable. In a preferred embodiment, the second step slurry formulation achieves removal rates of $> 1000 \text{ \AA}/\text{min}$ for the barrier material.
 25

The present invention provides a two-step polishing formulation comprising first and second-step slurry compositions, wherein said first-step slurry comprises an organic polymeric abrasive and said second-step slurry comprises an abrasive, and an oxidizing agent, wherein the abrasive component is selected from the group consisting of silica, alumina, ceria and mixtures thereof.
 30

Further, the instant invention relates to a second-step polishing slurry formulation comprising silica as abrasive particles, an oxidizing agent, and a passivating agent. The chemistry of the second-step slurry should be stable and have a pH in the range of about 4 to 10.

Prefereably, the particles of the second step slurry formulation are precipitated silica. The precipitated particles usually range from about 3 to 100 nm in size and can be spherical. An alternative to precipitated silica particles in the second-step slurry is fumed silica. Generally, the fumed silica has a mean particle size of less than 700 nm.

5

Alternatively, and more preferred is to use colloidal silica particles of the type described. The colloidal silica particles can range from about 3 to 70 nm in size, and can be spherical. Preferentially, when the first and second step slurries employ spherical colloidal particles, the particles should have a narrow size distribution. More specifically, about 99.9% of the spherical colloidal particles should be within about 3 sigma of a mean particle size with negligible particles larger than about 500 nm.

10

The second step slurry, thus, can employ either precipitated spherical silica particles in the size range of 3 to 100 nm, or fumed silica with mean particle size less than about 700 nm. These particles coupled with an oxidizing agent allow the second-step slurry to achieve high barrier material removal rates and low copper and dielectric removal rates (as shown in Table 1 heretofore). Colloidal silica, with a narrow size distribution, minimizes micro scratch defects and provides superior removal rates on barrier materials, greater than about 1000 Å/min, and low removal rates for copper and barrier. Further, spherical silica abrasives with a mean size of less than about 100 nm provide very good planarization efficiency (See Table 1, hereinabove).

15

20

The preferred oxidizing agent for the second step slurry is hydrogen peroxide (H_2O_2). Alternatively, the oxidizing agent may be selected from the group consisting of: ferric nitrate ($Fe(NO_3)_3$), potassium iodate (KIO_3), potassium permanganate ($KMnO_4$), nitric acid (HNO_3), ammonium chlorite (NH_4ClO_2), ammonium chlorate (NH_4ClO_3), ammonium iodate (NH_4IO_3), ammonium perborate (NH_4BO_3), ammonium perchlorate (NH_4ClO_4), ammonium periodate (NH_4IO_3), ammonium persulfate ($(NH_4)_2S_2O_8$), tetramethylammonium chlorite ($(N(CH_3)_4)ClO_2$), tetramethylammonium chlorate ($(N(CH_3)_4)ClO_3$), tetramethylammonium iodate ($(N(CH_3)_4)IO_3$), tetramethylammonium perborate ($(N(CH_3)_4)BO_3$), tetramethylammonium perchlorate ($(N(CH_3)_4)ClO_4$), tetramethylammonium periodate ($(N(CH_3)_4)IO_4$), tetramethylammonium persulfate ($(N(CH_3)_4)S_2O_8$), and urea hydrogen peroxide ($(CO(NH_2)_2)H_2O_2$).

25

30

Alternatively, the oxidizing agent of the second step slurry may comprise an amine-N-oxide having the formula $(R_1R_2R_3N \rightarrow O)$, wherein $R_1R_2R_3$ are independently selected from the group consisting of:

H and C₁-C₈ alkyl. Specific examples of amine-N-oxides include but are not limited to 4-methylmorpholine N-oxide (C₅H₁₁NO₂) and pyridine-N-oxide (C₅H₅NO).

The passivating agent as used in the second step slurry is defined as any substance which when mixed with the second-step slurry composition, suppresses etching, while permitting a sufficient CMP rate to be obtained. Preferably, the passivating agent in the second step slurry formulation is benzotriazole (referred to hereafter as BTA) or iminodiacetic acid (referred to hereafter as IDA). Other substances useful as passivating agents include but are not limited to: tolyltriazole, BTA derivatives, such as BTA carboxylic acids, cystine, haloacetic acids, glucose and dodecyl mercaptan.

The cleaning agent or complexing agent should be a carboxylic acid. More specifically, the carboxylic acid may be chosen from the group of glycine, oxalic acid, malonic acid, succinic acid, nitrilotriacetic acid, and citric acid. Alternatively, the complexing agent may be a dicarboxylic acid that preferentially has a nitrogen containing functional group or an amine. In the most preferred form, the complexing agent for the second-step slurry composition is iminodiacetic acid or ethylenediamine.

The second step-slurry composition may further comprise potassium or ammonium hydroxide or any weak organic base, such as tetramethyl ammonia, tetraethyl ammonia, and amines in such amounts as to adjust the pH to the desired level. Preferably, the pH of the second-step slurry composition is from about 7.1 to 10 and more preferably, from about 7.9 to 8.8.

In one embodiment, the second step-slurry composition comprises from about 0 to 30 percent oxidizer, about 1 to 10 percent colloidal silica or precipitated silica, about 0.01 to 5 percent complexing agent, and about 0 to 5 percent passivating agent, and water.

In a more preferred embodiment, the second step-slurry composition comprises from about 0 to 15 percent oxidizer, about 5 to 10 percent colloidal silica or precipitated silica, about 0.05 to 1 percent complexing agent, and about 0.02 to 0.1 percent passivating agent, and water.

In the most preferred embodiment, the second-step slurry composition, comprises 0.05 percent ethylenediamine as complexing agent and 5 percent colloidal silica.

Although the present invention is directed to removal of copper, copper containing materials and related barriers, it is not thus limited to such. The present invention is useful for polishing and

planarizing materials useful as interconnects and related barriers in semiconductor related applications including but not limited to aluminum, aluminum alloys, aluminum compounds having aluminum as its principal component, tungsten, tungsten alloys, tungsten compounds having tungsten as its principal component, (i.e., tungsten nitride), tantalum, tantalum nitride, silicon doped tantalum nitride, titanium, titanium alloys and titanium compounds having titanium as its principal component (i.e., titanium nitride and silicon doped titanium nitride).

It is further understood that the present invention is not limited to the particular embodiments shown and described herein, but that various changes and modifications may be made without departing from the scope and spirit of the invention.

The features, aspects and advantages of the present invention are further shown with reference to the following non-limiting examples relating to the invention.

Examples

The pH, oxidizing agents, modifying agents, abrasive particle composition and size distribution, and weight percent were evaluated to establish a baseline for removal rates and selectivity for the second step slurry formulations.

Example 1: Slurry 1 Formulations Showing Static Etch Rate of Copper

Several formulations of the first slurries were prepared. The static etch removal rates of these formulations are described in Table 4. As can be seen from Table 4, the first step slurry formulations of the present invention were effective in achieving acceptable static copper removal rates of 50 A/min.

Table 1. Removal Rate Under Static Conditions (SRR). Component Values in Weight Percent

Slurry	H ₂ O ₂	Citric Acid	IDA	IX-38	NH ₃	pH	SRR			
1	5		0.2			2.5	300 (2)			
2	5		0.1			2.6	237 (2)			
3	5			5		4.1	208 (5)			
4	5	1		5		2	N/A (5)			
5	5		0.2	5		2.3	N/A (5)			
6	5	1	0.2			2.1	1600 (2)	944 (3)		
7	5	1	0.2	5		2.2	N/A (5)			
8		0.5		5	0.00273	3.5	1.17 (1)			
9	5	0.5			0.00523	3.5	661 (1)			
10	5		0.2		0.00298	3.7	150 (1)	90 (2)		

11	5	0.5	0.2		0.00891	3.5	640 (1)	501 (3)		
12	5	0.5		5	0.00529	3.5	793 (1)			
13	5		0.2	5	0.003	3.6	149 (1)	98 (2)	70 (5)	
14	5	0.5	0.2	5	0.00885	3.5	858 (1)	627 (2)	453 (5)	
15	10	0.5	0.2	5	0.00912	3.5	1029 (1)	578 (2)	468 (5)	439 (10)
16	1	0.5	0.2	5	0.00851	3.5	855 (1)	666 (2)	563 (5)	520 (10)
17	5	0.25	0.5	5	0.01	3.5	601 (1)	488 (2)	450 (5)	
18	5	0.25	1	5	0.017	3.5	836 (1)	561 (2)	377 (5)	
19	5	0.25	0.5	5	0.44	3.5	960 (1)	504 (2)	300 (5)	298 (10)
20	5	0.1	0.1	5	0.022	3.5	260 (1)	181 (2)	159 (5)	199 (1)
21	5	0.1	0.2	5	0.032	3.5	424 (1)	273 (2)	138 (5)	
22	5			5		4				
23	5		0.2	5		2.3				
24	5		0.2	5	0.027	3.5				
25	5	0.1	0.2	5	0.013	2.5	528(1)	516 (2)	323(5)	
26	5	0.1	0.2	5	0.028	3	400(1)	285(2)		
27	5	0.1	0.2	5	0.041	3.5	273(1)	178(2)		

The numbers in parentheses indicate the length of soaking time for static etching rate study.

Example 2:

Table 3 outlines twelve formulations and polishing conditions for the second step polishing slurry tested on Ta, TaN, Cu and thermal oxide blanket wafers (**Table 4**). The various formulations comprise between 0 to 13 percent hydrogen peroxide (H_2O_2) as oxidizing agent, 0 to 0.05 percent ethylenediamine as complexing agent, between 0 to 0.1 percent BTA, or between 0 to 0.2 percent iminodiacetic acid as passivating agent, and between 5 to 10 percent colloidal silica or 5 to 10 percent precipitated silica. The pH of the formulations ranged from 6.8 to 8.8. The polishing conditions ranged from table speed (TS) of 45 to 125 rpm, quill speed (QS) of 42 to 116 rpm, down force (DF) of 3.5 to 4 psi, and a flow rate (FR) of 160 mL/min.

Table 3. Compositions and Polishing Conditions for Second Step Slurry

Slurry:	H_2O_2	EDA	BTA	IDA	Colloid al Silica	Precipitat ed Silica	KOH	pH	Polish Conditions TS/QS/DF/FR
1		0.05			5			8.8	125/116/4.0/160
2					5		*	6.8	125/116/4.0/160
3	0.5	0.05			5			6.8	45/42/3.5/160
4	13					10		8.1	125/116/4.0/160
5	13			0.2		10		6.8	125/116/4.0/160
6	13				10		*	6.7	45/42/3.5/160
7	13					10		7.9	45/42/4.0/160
8	13					5		8	45/42/4.0/160
9	13					15		8.1	45/42/4.0/160

10	13		0.02			10		8	45/42/4.0/160
11	13		0.005			10		8	45/52/4.0/160
12	0.5		0.1		5		*	8	45/42/4.0/160

*chemical used to adjust the pH

Table 4. Removal Rates (Å/min) and Selectivities Using Second Step Slurry Compositions Outlined in Table 3.

Slurry:	Cu	Ta	TaN	PETEOS	Ta:Cu:Oxide	TaN:Cu:oxide
1	116	130	1167	127	1:1:1	1:0.1:0.1
2	29	42	35	N/A	1:0.69	1:0.83
3	1071	567	622	43	1:1.89:0.076	1:1.72:0.069
4	138	562	659	667	1:0.25:1.19	1:0.21:1.01
5	812	562	1082	807	1:0.69:0.70	1:0.75:0.75
6	62	28	47	50	1:2.2:1.79	1:1.32:1.06
7	123	512	203	195	1:0.24:0.38	1:0.61:0.96
8	102	75	121	52	1:1.4:1.7	1:0.85:0.43
9	164	432	435	447	1:0.48:1.31	1:0.38:1.03
10	"1"	166	232	172	1:0.006:1.04	1:0.0043:0.74
11	"1"	162	197	170	1:0.0062:1.05	1:0.0051:0.86
12	"1"	60	81	31	1:0.017:0.52	1:0.012:0.38

As Table 4 indicates, a selectivity of TaN:Cu:PETEOS of 10:1:1 was obtained using Slurry 1. When Ta is the barrier material, two useful formulations were discovered. The first one was based on second step formulation, Slurry 7 as listed in this Table, which includes 13 wt % of H₂O₂ and 10 wt % of a precipitated silica abrasive. To this slurry, BTA (passivating agent) was added with concentrations of 0.005 wt % (Slurry 11) and 0.02 wt % (Slurry 10). With the modified Slurry 7 formulation, removal rates for Ta, TaN, Cu and PETEOS have all been reduced, with the largest decrease in copper. However, a selectivity of Ta:Cu of 166:1 has been obtained. The Slurry 12 formulation which employed a 5 wt % colloidal silica, 0.5 wt. % H₂O₂, 0.1.wt. % BTA with a pH of 8 obtained a Ta:Cu:PETEOS of 60:1:30.

Example 3: Stability Experiment

The poly (methyl methacrylate) colloid of the step one slurry formulation shows outstanding chemical and mechanical stability. The particles did not show any significant changes in terms of particle size and particle size distribution after aging two months, that is, the mean particle size remains about 45 nm and the range of distribution is from about 5 nm to 100 nm.

The first and second slurries described herein, may also be used in a method of chemical mechanical polishing as described above. Also, while this invention has been disclosed and discussed primarily in terms of specific embodiments thereof, it is not intended to be limited thereto. Other modifications and embodiments will be apparent to the skilled worker in the art.

11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2213
2214
2215
2216
2217
2218
2219
2220
2221
2222